

Lantech.com

S - 300

Semi-Automatic Straddle
Stretch Wrapping System



Productivity

Improve:

Customer Satisfaction

Product Protection

Operator Efficiency



Product Applications

- Light Loads
- High Volume
- Heavy Loads
- Tall Unstable Loads

Create Your Own System

Configure and price a stretch wrapper at www.lantech.com.

Q-300



ABCO KOVEX
POWERFUL PACKAGING SOLUTIONS

T +353.1.807 7600

F +353 1 807 7650

E sales@abcokovex.com

To see our full range of products go to
www.abcokovex.com

Go on
Figure

S-300

The S-300 Advantages



AutoFilm Cut-off™

Keep operator on forklift, increasing productivity.



Safety Shield

Large safety shield is a shock-absorbing device, which immediately stops the rotating wrap arm to prevent injury.



Wrapping Clearance

35 cm safety clearance between the column and the rotating arm in case someone enters this area.

Free Standing

Design eliminates vibration, stress and potential structural damage that can result with wall-mounted systems.

S-300 Specifications

PERFORMANCE CRITERIA

■ Production Speed based on 2030 mm load height; 2 film layers and 12 revolutions	25-35 loads per hour
■ Maximum Load Size (l x w x h)	1473 x 1473 x 2032 mm
■ Minimum Load Size (l x w x h)	762 x 762 x 508 mm
■ Maximum Load Weight	Floor capacity

LOAD HANDLING SYSTEM

■ Turntable Drive	0,55 kW
■ Turntable Speed	1-12 RPM

FILM DELIVERY SYSTEM

■ Power-Roller Stretch® System	200% Standard, 100-300% Available
■ Wrapping Force	Electronically Controlled
■ Film Capacity	250 mm diameter, 500 mm film web width
■ E-Z Thread Roll Carriage	Standard

ELECTRICAL REQUIREMENTS

■ Machine Voltage	240 V, 16 A
■ Microcontroller	Standard
■ CE/IP52 enclosure	Standard

Specifications subject to change without notice. Lantech systems and sub-systems are protected by U.S. and foreign patents. Additional U.S. and foreign patents pending. © Lantech 2003

307 cm
HEIGHT

